


# ESSENTIAL SMART BRIGHT PROJECTOR



## Features

System efficiency, up to 85 lm/W  
 Beam Angle: 24° & 36°  
 High reliability, 20 khrs (L70B50@25 °C)  
 Color options: Black / White

## Application

Retail shop  
 Fashion outlet  
 Shopping centre

## Model

Model	ST030T LED8	ST030T LED12	ST030T LED20	ST030T LED30
Size (H2 x L x W)	174mm x 130mm x 52mm	174mm x 130mm x 52mm	178mm x 130mm x 52mm	192mm x 180mm x 60mm
Nominal Power	8W	14W	23W	35W
System Flux	800lm	1,200lm	2,000lm	3,000lm

\* System lumen refers to typical lumen output of NW(4000K) product, it could result less lumen in WW(3000K) or higher lumen in CW(6500K).

## Specifications

Model	ST030T LED8	ST030T LED12	ST030T LED20	ST030T LED30
Input Voltage	220-240V, 50/60Hz			
Beam angle	24° / 36°			
Lifetime	20,000 hours (L70B50 @ 25°C)			
CCT	3000K / 4000K / 5000K			
Weight (kg)	0.33 kg	0.33 kg	0.43 kg	0.63 kg
IP Rating	IP20			
Power Factor	> 0.9			
Color Index	> 80			
Materials & Finishing	Aluminium housing; Polymethyl methacrylate optic material Black / White finishing			
Operating Temp.	- 20 °C < Ta < + 40 °C			
Mounting Type	Surface Mounting			
Standard	CE, RoHS			



Track accessories for track light need to be purchased separately. Available in 1000mm and 2000mm