


# ESSENTIAL SMARTBRIGHT SURFACE MOUNTED LED DOWNLIGHT

DOWNLIGHT



CE IP40

## Features

System efficiency, up to 85 lm/W  
CRI 80+, SDCM < 5  
High reliability, 20 khrs (L70B50@25 °C)

## Application

Retails  
Office  
Residential

## Model

Model	DN027C/SM-9	DN027C/SM-12	DN027C/SM-15	DN027C/SM-20
Size (D x h)	150mm x 40mm	175mm x 40mm	200mm x 40mm	225mm x 40mm
Nominal Power	11W	15W	18W	23W
System Flux	900lm	1,200lm	1,500lm	2,000lm

\* System lumen refers to typical lumen output of NW(4000K) product, it could result less lumen in WW(3000K) or higher lumen in CW(6500K).

## Specifications

Model	DN027C/SM-9	DN027C/SM-12	DN027C/SM-15	DN027C/SM-20
Input Voltage	220-240V, 50/60Hz			
Beam angle	110°			
Lifetime	20,000 hours (L70B50 @ 25°C)			
CCT	3000K / 4000K / 6500K			
Weight (kg)	0.36 kg	0.46 kg	0.57 kg	0.69 kg
IP Rating	IP20 / IP40 (Front part)			
Power Factor	Up to 0.75			
Color Index	> 80			
Materials & Finishing	Metal housing with RAL9003 white painting, PC white (RAL9003) back cover; PC light diffuser			
Operating Temp.	- 20 °C < Ta < + 40 °C			
Mounting Type	Recessed Mounting			
Standard	CB, EMC, CCC, (TISI, KC)			