


# SMARTBRIGHT G2 LED FLOODLIGHT



## Features

High system efficacy  
 Long lifetime, 50 khrs @ Ta 25°C  
 Robust design, Die-cast housing, Front Glass

## Application

Parking Area  
 Landscape  
 Billboard

## Model

Model	BVP151-100W	BVP151-150W	BVP151-200W
Size (A x B x C)	236mm x 360mm x 58mm	293mm x 430mm x 60mm	336mm x 491mm x 60mm
Nominal Power	100W	150W	200W
System Flux	10,000lm	15,000lm	20,000lm

\* System lumen refers to typical lumen output of NW(4000K) product, it could result less lumen in WW(3000K) or higher lumen in CW(6500K).

## Specifications

Model	BVP151-100W	BVP151-150W	BVP151-200W
Input Voltage	220-240V, 50/60Hz		
Beam angle	Asymmetrical Wide Beam (40° x 80°)		
Lifetime	50,000hrs (L70B50@Ta25°C)		
CCT	3000K / 4000K / 5700K		
Weight (kg)	3.28 kg	5.02 kg	6.26 kg
IP Rating	IP65		
Power Factor	> 0.9		
Color Index	> 80		
Materials & Finishing	Housing: Die-cast aluminium powder coated dark grey (RAL7043)   Front cover: Tempered glass   Bracket: Steel powder coated dark grey (RAL7043)		
Operating Temp.	- 25 °C to + 40 °C		
Mounting Type	Bracket mounting		
Standard	CE, CQC, CB, EMC, AS/NZS60598		